

ENGINEERING DEPARTMENT
UNIVERSITY OF DELHI

Ref no. UE/ **118** / DU/ M-54 (2016-17) dated

15/7/16

Sealed ~~rate~~ ^{page} rate quotations are here by invited from Contractors enlisted with CPWD, MES, Railways and working Contractors of Delhi University for the work" Replacing damaged / broken floor and other misc works in flat no. C-22 at 29-31 Probyn road , University of Delhi, So as to reach the office of the Undersigned at 3.00 PM on dated :18.7.2016

| S.No | Description of item | Qty | Unit | Rate | Amount |
|------|--|-----|------|---------|--------|
| 1 | Demolishing cement concrete manually/ by mechanical means including disposal of material within 50 metres lead as per direction of Engineer - in Nominal concrete 1:3:6 or richer mix (i/c equivalent design mix) | 1.2 | sq m | 892.7 | 1071 |
| 2 | Dismantling old plaster or skirting raking out joints and cleaning the surface for plaster including disposal of rubbish to the dumping ground within 50 metres lead. | 30 | sq m | 20.05 | 602 |
| 3 | Kota stone slab flooring over 20 mm (average) thick base laid over and jointed with grey cement slurry mixed with pigment to match the shade of the slab, including rubbing and polishing complete with base of cement mortar 1 : 4 (1 cement : 4 coarse sand) : 25 mm | 45 | sqm | 1141.4 | 51363 |
| 4 | Kota stone slabs 20 mm thick in risers of steps, skirting, dado and pillars laid on 12 mm (average) thick cement mortar 1:3 (1 cement: 3 coarse sand) and jointed with grey cement slurry mixed with pigment to match the shade of the slabs, including rubbing and polishing complete. | 4 | sqm | 1191.25 | 4765 |
| 5 | Providing and laying in position cement concrete of specified grade excluding the cost of centering and shuttering - All work up to plinth level : 1:5:10 (1 cement : 5 coarse sand : 10 graded stone aggregate 40 mm nominal size) | 1 | cum | 4004 | 4004 |
| 6 | Providing and laying vitrified floor tiles in different sizes (thickness to be specified by the manufacturer) with water absorption less than 0.08% and conforming to IS : 15622, of approved make, in all colours and shades, laid on 20mm thick cement mortar 1:4 (1 cement : 4 coarse sand), including grouting the joints with white cement and matching pigments etc., complete. Size of Tile 500x500 mm | 30 | sq m | 1310.7 | 39321 |
| 7 | Taking out and refixing again after repairing the existing m.s grill gate including changing the m.s.hinges , alignment , adjustment and making functional etc complete as per given direction at site | 2 | job | 500 | 1000 |
| 8 | Taking out and refixing again the wooden door shutters after repairing changing panel , cutting , screwing , nailing , adjustment and making functional etc complete as per given direction at site .(panelling will be paid separetly) | 3 | job | 350 | 1050 |
| 9 | Providing and fixing panelling or panelling and glazing in panelled or | | | | |

| | | | | | |
|----|--|-----|------|---------|-------|
| | panelled and glazed shutters for doors, windows and clerestory windows (Area of opening for panel inserts excluding portion inside grooves or rebates to be measured). Panelling for panelled or panelled and glazed shutters 25 mm to 40 mm thick : Decorative plywood one side decorative veneer and commercial veneer on other face (Type 1) conforming to IS 1328 BWR Type Ply wood 7 ply, 9 mm thick | 5 | sqm | 1652.6 | 8263 |
| 10 | Providing and fixing ISI marked M.S. pressed butt hinges bright finished with necessary screws etc. complete : 125x65x2.12 mm | 12 | each | 33.65 | 404 |
| 11 | Providing and fixing fly proof stainless steel grade 304 wire gauge, to windows and clerestory windows using wire gauge with average width of aperture 1.4 mm in both directions with wire of dia. 0.50 mm all complete. With 12 mm mild steel U beading | 10 | sq m | 1317.55 | 13176 |
| 12 | Steel work welded in built up sections/ framed work, including cutting, hoisting, fixing in position and applying a priming coat of approved steel primer using structural steel etc. as required. In gratings, frames, guard bar, ladder, railings, brackets, gates and similar works | 30 | kg | 90.1 | 2703 |
| 13 | Distempering with oil bound washable distemper of approved brand and manufacture to give an even shade : New work (two or more coats) over and including water tinnable priming coat with cement primer | 100 | sq m | 89.7 | 8970 |
| 14 | Applying priming coat : With ready mixed pink or Grey primer of approved brand and manufacture on wood work (hard and soft wood) | 10 | sq m | 32.95 | 330 |
| 15 | Repairs to plaster of thickness 12 mm to 20 mm in patches of area 2.5 sq. meters and under, including cutting the patch in proper shape, raking out joints and preparing and plastering the surface of the walls complete, including disposal of rubbish to the dumping ground within 50 metres lead : With cement mortar 1:4 (1cement: 4 coarse sand) | 10 | sq m | 259.15 | 2592 |
| 16 | Renewing glass panes, with putty and nails wherever necessary including racking out the old putty: Float glass panes of thickness 4 mm | 2 | sqm | 690.7 | 1381 |
| 17 | Distempering with oil bound washable distemper of approved brand and manufacture to give an even shade : Old work (one or more coats) | 200 | sq m | 32 | 6400 |
| 18 | Removing dry or oil bound distemper, water proofing cement paint and the like by scrapping, sand papering and preparing the surface smooth including necessary repairs to scratches etc. complete. | 100 | sqm | 9.9 | 990 |

| | | | | | |
|----|---|-----|------|-------|--------|
| 19 | Painting (one or more coats) on rain water, soil, waste and vent pipes and fittings with black anticorrosive bitumastic paint of approved brand and manufacture on old work : | | | | |
| a | 75 mm diameter pipes | 10 | m | 12.45 | 125 |
| b | 100 mm diameter pipes | 10 | m | 16.35 | 164 |
| 20 | Painting with synthetic enamel paint of approved brand and manufacture of required colour to give an even shade : | | | | |
| | One or more coats on old work | 200 | sq m | 48.5 | 9700 |
| 21 | Finishing walls with Acrylic Smooth exterior paint of required shade : | | | | |
| | Old work (Two or more coat applied @ 1.67 ltr/ 10 sqm) on existing cement paint surface | 200 | sq m | 67.3 | 13460 |
| 22 | Cleaning and granit polishing on existing marble work/Granite work/stone work where ever required to give high gloss finish complete. | 55 | sq m | 100 | 5500 |
| 23 | Providing and fixing shelves / partition as per requirement , rods etc in the existing steel almirah including cost of lock , keys and other other fittings with making spray painting etc complete as per direction of Engineer in charge (size 1.33 sqm to 2.20 sqm face area) | 5 | job | 3900 | 19500 |
| 24 | Disposal of malba or building rubbish from site to out side the campus by mechanical transport including laoding and unloading etc complete | 10 | cum | 300 | 3000 |
| | | | | | 199831 |

Conditions :-


1. The work is to be completed with 30 days
2. 1.50 % water charges will be deducted
3. CPWD Specifications will be followed
4. Rates should be quoted both in words & figures.
5. Undersigned reserves the authority to reject any or all the quotation without any reason therefore .
6. SC/ST Contractors shall enclosed copies of attested cast certificate other wise there quotation will be accepted.
7. Contractor shall enclosed the copy of Labour Licence Registration with ETFO , ESIC and BOCW welfare board other wise there quotation will not be accepted .

Executive Engineer

I hereby quote % rate above / below / At par on estimated cost of Rs.199831.00

Contractor

1. The Director computer center with a request to display the inviting quotation on the University of Delhi website.
- ✓ 2. Mrs. Kavita , JACT , for information and to ensure the display of the quotation on University website.
3. Section Officer -II
4. Notice Board


Executive Engineer