

**ENGINEERING DEPARTMENT  
UNIVERSITY OF DELHI  
DELHI-110007**

**NOTICE INVITING QUOTATIONS  
dated**

15/9/14

Ref. No. UE/ 154


/DU/M- 54 (2014-2015)

Sealed item rate quotation are hereby invited from the contractor enlisted with CPWD, MES, Railways and any Govt. sector undertaking and working contractor of Delhi University for the work "Repair/ renovation of flat no. 38/22 at 38 Probyn Road, University of Delhi." 'So as to reach the office of the undersigned upto 3.00 P.M. on 19.09.2014

| S. No | Description of Items  | Unit | Qty | Rate         | Amount     |
|-------|---|------|-----|--------------|------------|
| 1     | Providing and fixing fly proof stainless steel grade 304 wire gauge, to windows and clerestory windows using wire gauge with average width of aperture 1.4 mm in both directions with wire of dia. 0.50 mm all complete. With 2nd class teak wood beading 62X19 mm  | sqm  | 5   |              |            |
| 2     | Providing and fixing 1st quality ceramic glazed wall tiles conforming to IS: 15622 (thickness to be specified by the manufacturer), of approved make, in all colours, shades except burgundy, bottle green, black of any size as approved by Engineer-in-Charge, in skirting, risers of steps and dados, over 12 mm thick bed of cement mortar 1:3 (1 cement : 3 coarse sand) and jointing with grey cement slurry @ 3.3kg per sqm, including pointing in white cement mixed with pigment of matching shade complete. | sqm  | 40  |              |            |
| 3     | Distempering with oil bound washable distemper of approved brand and manufacture to give an even shade : New work (two or more coats) over and including water thinnable priming coat with cement primer  | sqm  | 350 |              |            |
| 4     | Painting with synthetic enamel paint of approved brand and manufacture to give an even shade : Two or more coats on new work  | sqm  | 220 |              |            |
| 5     | Providing and applying white cement based putty of average thickness 1 mm, of approved brand and manufacturer, over the plastered wall surface to prepare the surface even and smooth complete.   | sqm  | 280 |              |            |
| 6     | Repairs to plaster of thickness 12 mm to 20 mm in patches of area 2.5 sq. meters and under, including cutting the patch in proper shape, raking out joints and preparing and plastering the surface of the walls complete, including disposal of rubbish to the dumping ground within 50 metres lead : With cement mortar 1:4 (1 cement : 4 fine sand)  | sqm  | 2   |              |            |
| 7     | Removing dry or oil bound distemper, water proofing cement paint and the like by scrapping, sand papering and preparing the surface smooth including necessary repairs to scratches etc. complete.  | sqm  | 350 |              |            |
| 8     | Dismantling old plaster or skirting raking out joints and cleaning the surface for plaster including disposal of rubbish to the dumping ground within 50 metres lead.   | sqm  | 40  |              |            |
| 9     | Disposal of building rubbish/ malb/ similar unserviceable/ malba / similar unserviceable, dismantled or waste material by mechanical means, i/c loading & unloading as approved by Engineer-in-charge i/c cartage upto 12 km  | cum  | 5   |              |            |
| 10    | Providing and fixing wash basin with C.I. brackets, 15 mm C.P. brass pillar taps, 32 mm C.P. brass waste of standard pattern, including painting of fittings and brackets, cutting and making good the walls wherever require White Vitreous China Flat back wash basin size 550x 400 mm with single 15 mm C.P. brass pillar tap  | each | 2   |              |            |
| 11    | Providing and fixing Stainless Steel A ISI 304 (18/8) kitchen sink as per IS : 13983 with C.I. brackets and stainless steel plug 40 mm, including painting of fittings and brackets, cutting and making good the walls wherever required Kitchen sink without drain board 610x460 mm bowl depth 200 mm  | each | 1   |              |            |
| 12    | Providing and fixing P.V.C. waste pipe for sink or wash basin including P.V.C. waste fittings complete. Flexible pipe 32 mm dia   | each | 3   |              |            |
| 13    | Providing and fixing 600x450 mm beveled edge mirror of superior glass (of approved quality) complete with 6 mm thick hard board ground fixed to wooden cleats with C.P. brass screws and washers complete.  | each | 1   |              |            |
| 14    | Providing and fixing C.P. brass bib cock of approved quality conforming to IS:8931 15 mm nominal bore   | each | 8   |              |            |
| 15    | Providing and fixing C.P. brass angle valve for basin mixer and geyser points of approved quality conforming to IS:8931 a) 15 mm nominal bore 15mm nominal bore   | each | 4   |              |            |
| 16    | Providing and fixing unplasticised P.V.C. connection pipe with PTMT Nuts, collar and bush of approved quality and colour. 15 mm nominal bore with 30cm length   | each | 6   |              |            |
|       |   |      |     | <b>Total</b> | <b>Rs.</b> |

**Condition:**

- The work should be completed in 10 days.
- 1.50 % water charges will be deducted.
- Rates should be quoted both in words & figures.
- CPWD specification in force will be followed.
- Undersigned reserves the authority to reject any or all the quotation without assigning any reason therefore.


  
Executive Engineer

**Undertaking:**

I/we hereby undertake that my/our agency have not been black listed/debarred in any Govt. organization since last 3 years.

**(Contractor)**

- The Director, Computer Center with a request to display the Notice Inviting Quotation on the Delhi University Website.
- Mrs. Kavita, J.A.C.T. to ensure the display of the tender/ quotation notice on University website
- Notice Board.

  
Executive Engineer