

ENGINEERING DEPARTMENT
UNIVERSITY OF DELHI
DELHI-110007

NOTICE Re- INVITING QUOTATIONS
(2015-2016)

dated

18/11/15

Ref. No. UE/ 322 /DU/M-54

Sealed item rate quotations are hereby Re-invited from the contractors enlisted with CPWD, MES, Railways and working contractor of Delhi University for the work "Distemping, painting, vitrified floor tiles etc at A-2 (29-31) Probyn Road, University of Delhi " So as to reach the office of the undersigned upto 3.00 P.M. on

24-11-15

| No | Description of Items | Unit | Qty | Rate | Amount |
|----|---|------|-----|------|--------|
| 1 | Providing and fixing 18 mm thick gang saw cut, mirror polished, premoulded and prepolished, machine cut for kitchen platforms, vanity counters, window sills, facias and similar locations of required size, approved shade, colour and texture laid over 20 mm thick base cement mortar 1:4 (1 cement : 4 coarse sand), joints treated with white cement, mixed with matching pigment, epoxy touch ups, including rubbing, curing, moulding and polishing to edges to give high gloss finish etc. complete at all levels. Granite of any colour and shade Area of slab over 0.50 sqm | sqm | 7 | | |
| 2 | Extra for fixing marble /granite stone, over and above corresponding basic item, in facia and drops of width upto 150 mm with epoxy resin based adhesive, including cleaning etc. complete. | mtr | 8 | | |
| 3 | Extra for providing opening of required size & shape for wash basin/ kitchen sink in kitchen platform, vanity counter and similar location in marble/ Granite/stone work, including necessary holes for pillar taps etc. including moulding, rubbing and polishing of cut edges etc. complete. | each | 1 | | |
| | High polishing on marble work/Granite work/stone work where ever required to give high gloss finish complete. | sqm | 140 | | |
| 5 | Providing and laying vitrified floor tiles in different sizes (thickness to be specified by the manufacturer) with water absorption less than 0.08% and conforming to IS : 15622, of approved make, in all colours and shades, laid on 20mm thick cement mortar 1:4 (1 cement : 4 coarse sand), including grouting the joints with white cement and matching pigments etc., complete. Size of Tile 600x600 mm | sqm | 90 | | |
| 6 | Providing and fixing 1st quality ceramic glazed wall tiles conforming to IS: 15622 (thickness to be specified by the manufacturer), of approved make, in all colours, shades except burgundy, bottle green, black of any size as approved by Engineer-in-Charge, in skirting, risers of steps and dados, over 12 mm thick bed of cement mortar 1:3 (1 cement : 3 coarse sand) and jointing with grey cement slurry @ 3.3kg per sqm, including pointing in white cement mixed with pigment of matching shade complete | sqm | 80 | | |
| 7 | Providing and laying Ceramic glazed floor tiles of size 300x300 mm (thickness to be specified by the manufacturer) of 1st quality conforming to IS : 15622 of approved make in colours such as White, Ivory, Grey, Fume Red Brown, laid on 20 mm thick cement mortar 1:4 (1 Cement : 4 Coarse sand), including pointing the joints with white cement and matching pigment etc, complete. | sqm | 20 | | |
| 8 | 12 mm cement plaster of mix : 1:6 (1 cement: 6 fine sand) | sqm | 50 | | |
| 9 | 15 mm cement plaster on rough side of single or half brick wall of mix 1:6 (1 cement: 6 coarse sand) | sqm | 20 | | |
| 10 | 15 mm cement plaster on the rough side of single or half brick wall of mix : 1:6 (1 cement: 6 fine sand) | sqm | 50 | | |
| 11 | Cement plaster 1:3 (1 cement: 3 coarse sand) finished with a floating coat of neat cement. 12 mm cement plaster | sqm | 30 | | |
| 12 | Finishing walls with Acrylic Smooth exterior paint of required shade New work (Two or more coat applied @ 1.67 ltr/10 sqm over and including priming coat of exterior primer applied @ 2.20kg/ 10 sqm) | sqm | 200 | | |
| 13 | Wall painting with acrylic emulsion paint of approved brand and manufacture to give an even shade : Two or more coats on new work | sqm | 500 | | |
| 14 | Painting with synthetic enamel paint of approved brand and manufacture to give an even shade : Two or more coats on new work | sqm | 250 | | |

| | | | |
|----|---|-----|-----|
| 15 | Removal of plaster of thickness 12 mm to 20 mm in patches of area 2.5 sq. meters and under, including cutting the patches, preparing, raking out joints and preparing and plastering the surface of the walls complete, including disposal of rubbish to the dumping ground within 50 metres lead : With cement mortar 1:4 (1 cement : 4 fine sand) | sqm | 5 |
| 16 | Removing dry or oil bound distemper, water proofing cement paint and the like by scrapping, sand papering and preparing the surface smooth including necessary repairs to scratches etc. complete. | sqm | 500 |
| 17 | Dismantling old plaster or skirting raking out joints and cleaning the surface for plaster including disposal of rubbish to the dumping ground within 50 metres lead. | sqm | 150 |
| 18 | Disposal of building rubbish / malba / similar unserviceable, dismantled or waste materials by mechanical means, including loading, transporting, unloading to approved municipal dumping ground or as approved by Engineer-in charge, beyond 50 m initial lead, for all leads including all lifts involved. | cum | 5 |
| 19 | Providing and applying white cement based putty of average thickness 1 mm, of approved brand and manufacturer, over the plastered wall surface to prepare the surface even and smooth complete. | sqm | 500 |
| 20 | Demolishing cement concrete manually/ by mechanical means including disposal of material within 50 metres lead as per direction of Engineer - in - charge. Nominal concrete 1:4:8 or leaner mix (i/c equivalent design mix) | cum | 2.5 |
| 21 | Applying one coat of water thinnable cement primer of approved brand and manufacture on wall surface : Water thinnable cement primer | sqm | 500 |

Total Rs.

Condition:

- The work should be completed in 30 days.
- 1.50% water/ electric charges will be deducted.
- Rates should be quoted both in words & figures.
- Undersigned reserves the authority to reject any or all the quotation without assigning any reason therefore
- SC/ST contractors should enclose copies of attested caste certificate otherwise their quotation will not be considered.
- Contractor should enclose the copy of Labour Licence, Registration with EPFO, ESIC & BOCW Welfare Board otherwise their quotation will not be considered

Undertaking:

I/we hereby undertake that my/our agency have not been black listed/debarred in any Govt. organization since last 3 years.

Executive Engineer

Contractor

- The Director, Computer Center with a request to display the Notice Inviting Quotation on the Delhi University Website.
- Ms. Kavita, J.A.C.T. to ensure the display of the tender notice on University website
- Notice Board.

Executive Engineer